



Katalog-Nr. Cat.-No.							1854C		
P							☐		
M							☐		
K							■		
N							☐		
S							☐		
H							■		
d ₁	l ₂	l ₁	l ₃	d ₂	z	r	Ident No.	LMT-Code	
kurz short									
4	5	57	14,5	6	2	2	7172234	EM-HSCSF2 4x5/57 2BA	
6	7,5	57	21	6	2	3	7172235	EM-HSCSF2 6x7.5/57 2BA	
8	10	63	27	8	2	4	7172236	EM-HSCSF2 8x10/63 2BA	
10	12,5	72	32	10	2	5	7172237	EM-HSCSF2 10x12.5/72 2BA	
12	15	83	38	12	2	6	7172238	EM-HSCSF2 12x15/83 2BA	
lang long									
4	5	80	19	6	2	2	7172239	EM-HSCSF2 4x5/80 2BA	
6	7,5	90	54	6	2	3	7172240	EM-HSCSF2 6x7.5/90 2BA	
8	10	100	64	8	2	4	7172241	EM-HSCSF2 8x10/100 2BA	
10	12,5	100	60	10	2	5	7172242	EM-HSCSF2 10x12.5/100 2BA	
12	15	110	65	12	2	6	7172243	EM-HSCSF2 12x15/110 2BA	

Schnittwertempfehlungen ab Seite 4
Cutting data recommendations starting page 4

■ = Hauptanwendung First choice
☐ = Nebenanwendung Alternative

Der S-Schliff im Zentrum der Stirnschneide ermöglicht optimale Schnittwerte und garantiert beste Oberflächengüten.

The S-cut in the center of the front cutting edge enables optimized cutting data to ensures high class surface qualities.

